



DEGRIP S 50: SYNTHETIC SUPER-PENETRATING OIL

Recommended for removing rust from bolts, zip-seals, mechanisms, rusty components, etc.

Protects against rust and lubricates supports.

Can be used where conventional rust removers are not operable.

For disassembling severely seized and rusted components, such as screw fittings, bolts, regulator parts, bearings.

USERS:

Maintenance workshops, leisure divers, nautical organisations, etc.

CHARACTERISTICS:

- *Colour: Yellow DIN ISO 2049*
- *Base: Synthetic oil*
- *Density at 20°C: 0.83 g/cm³ in house*
- *Kinematic viscosity at 40°C: 2.8 mm²/s DIN 51562*
- *COC ignition: 70 °C DIN ISO 2592*
- *Wide temperature range: - 20 – + 80 °C*

ADVANTAGES:

- *Facilitates disassembly: enables fast, easy disassembly*
- *Excellent penetrating properties: penetrates even into extremely narrow spaces*
- *Good lubricating power*
- *Fast, reliable unblocking*
- *Cost-effective use*

METHOD OF USE:

Apply by manual spraying or with a brush. Leave the product to penetrate and act.

Shake well before use. Use-by date: 2 years

PACKAGING:

400mL aerosol

USE PRECAUTIONS:

Classification according to regulation (EC) No. 1272/2008

H229 Pressurised container: may burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

The product is classified and labelled according to the CLP regulation.

Hazard pictograms none

Warning statement Attention

Hazard statements: H229 Pressurised container: may burst if heated.

Safety advice

P210 Keep away from heat, hot surfaces, sparks, naked flames and any other source of ignition. Do not smoke.

P251 Do not pierce or burn, even after use.

P410+P412 Keep out of direct sunlight. Do not expose to temperatures above 50 °C/122 °F.

· Additional indications:

Contains 10.0% by weight of flammable components.